

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|---|-------------|----------------------|---------------------|------------------|
| 10/531,038 | 04/12/2005 | Joseph P Kennedy JR. | GRA26 009 | 4700 |
| Duane Morris 1667 K Street N W Suite 700 Washington, DC 20006 | | | EXAMINER | |
| | | | WENDELL, ANDREW | |
| | | | ART UNIT | PAPER NUMBER |
| | | | 2618 | |
| | | | | · |
| SHORTENED STATUTORY PERIOD OF RESPONSE | | MAIL DATE | DELIVERY MODE | |
| 3 MONTHS | | 02/23/2007 | PAPER | |

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

| | | Application No. | Applicant(s) | | | |
|--|--|---|--|--|--|--|
| Office Action Summary | | 10/531,038 | KENNEDY ET AL. | | | |
| | | Examiner | Art Unit | | | |
| | | Andrew Wendell | 2618 | | | |
| | The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply | | | | | |
| | ORTENED STATUTORY PERIOD FOR REPLY | / IS SET TO EXDIDE 2 MONTH/ | S) OR THIRTY (30) DAVS | | | |
| WHIC - Exter after - If NO - Failu Any I | CHEVER IS LONGER, FROM THE MAILING DANISIONS of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. It period for reply is specified above, the maximum statutory period were to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing and patent term adjustment. See 37 CFR 1.704(b). | ATE OF THIS COMMUNICATION 16(a). In no event, however, may a reply be tirr rill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE | N. nely filed the mailing date of this communication. D (35 U.S.C. § 133). | | | |
| Status | | | | | | |
| 1)🖂 | Responsive to communication(s) filed on 30 No | ovember 2006. | | | | |
| 2a) <u></u> □ | This action is FINAL . 2b)⊠ This action is non-final. | | | | | |
| 3) | Since this application is in condition for allowance except for formal matters, prosecution as to the merits is | | | | | |
| | closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213. | | | | | |
| Dispositi | on of Claims | | | | | |
| 4)⊠ | 4)⊠ Claim(s) <u>1,2,4-6,9,10,12-24 and 26-35</u> is/are pending in the application. | | | | | |
| | 4a) Of the above claim(s) is/are withdrawn from consideration. | | | | | |
| • | 5) Claim(s) is/are allowed. | | | | | |
| | Claim(s) <u>1-2, 4-6, 9-10, 12-24, and 26-35</u> is/are | e rejected. | | | | |
| • | Claim(s) is/are objected to. | alastian raquiroment | | | | |
| اــا(٥ | Claim(s) are subject to restriction and/or | election requirement. | | | | |
| Application Papers | | | | | | |
| 9) The specification is objected to by the Examiner. | | | | | | |
| 10) | 10) ☐ The drawing(s) filed on is/are: a) ☐ accepted or b) ☐ objected to by the Examiner. | | | | | |
| | Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). | | | | | |
| Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152. | | | | | | |
| Priority u | ınder 35 U.S.C. § 119 | | | | | |
| 12)⊠ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a)⊠ All b)□ Some * c)□ None of: | | | | | | |
| | 1.⊠ Certified copies of the priority documents have been received. | | | | | |
| 2. Certified copies of the priority documents have been received in Application No | | | | | | |
| | 3. Copies of the certified copies of the priority documents have been received in this National Stage | | | | | |
| application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. | | | | | | |
| | the attached detailed Office action for a list of | or the certified copies flot receive | u. | | | |
| Attachmen | t(s) | | | | | |
| | e of References Cited (PTO-892) | 4) Interview Summary | | | | |
| 3) Inform | e of Draftsperson's Patent Drawing Review (PTO-948) nation Disclosure Statement(s) (PTO/SB/08) r No(s)/Mail Date | Paper No(s)/Mail Da 5) Notice of Informal P 6) Other: | | | | |

Application/Control Number: 10/531,038

Art Unit: 2618

DETAILED ACTION

Claim Rejections - 35 USC § 112

1. The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

2. Claim 30 is rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. "disregarding a second signal received from the mobile appliance at each of the plural base stations when determining the location of the mobile appliance" was not found to be supported in the specification.

Claim Rejections - 35 USC § 102

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 1. Claims 22-23 are rejected under 35 U.S.C. 102(e) as being anticipated by Stein et al. (US Pat Appl# 2003/0008663).

Regarding claim 22, Stein et al. teaches a method of determining the location of a mobile appliance in a wireless communication system (Section 0007) having plural base stations 104a-c (Fig. 1A) and at least one repeater station 114a (Fig. 1A) for communicating with the mobile appliance 106 (Fig. 1A), wherein each of the at least

one repeater station are connected to a respective one of the plural base stations with a communication tether (Section 0024), the improvement comprising the steps of detecting signals (identification code) from a target mobile appliance on the communication tether (Sections 0008 and 0039-0040) and using a known delay (Section 0009) attributed to the communication tether (Section 0024) and the respective at least one repeater station to determine the location of the target mobile appliance (Sections 0026-0028, 0035, 0039-0040, and 0047).

Page 3

Regarding claim 23, Stein et al. teaches detecting signals from the target mobile appliance on another of the at least one repeater station's communication tether and using another known delay attributed to the another repeater station and the respective communication tether to determine the location of the target mobile appliance (Sections 0028, 0035, 0039-0040, and 0047).

Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stein et al. (US Pat Appl# 2003/0008663) in view of Kennedy, Jr. (US Pat# 6,952,158).

Regarding claim 1, Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources teaches in a method of determining the location of a mobile appliance in a wireless communication system (Fig.

1A) having plural base stations 104a-c (Fig. 1A) and at least one repeater 114a (Fig. 1A) for communicating with the mobile appliance 106 (Fig. 1A), where the wireless communication system has a network overlay geolocation system (Fig. 1A) operably connected thereto, the improvement of determining (identification code) whether a signal received from the mobile appliance by the geolocation system has passed through a first repeater (Sections 0007-0009 and 0039-0040), wherein plural signals are received from the mobile appliance by the geolocation system and the step of determining if one of the plural signals has passed through the first repeater is based in part on a difference between the times of arrival of two of the plural signals at the geolocation system (Sections 0026-0028 and 102-104). In Section 0028, Stein teaches receiving plurality of signals and using any combination of the signals to do a measurement. It would be obvious that with the plural of signals a combination could be taking two of the signals and doing a measurement of difference between the two signals. Even though it would be obvious, Stein fails to clearly teach step of determining based in part on a difference between the times of arrival of two of the plural signals at the geolocation system.

Kennedy teaches step of determining based in part on a difference between the times of arrival of two of the plural signals at the geolocation system (Col. 1 lines 16-30). Again, it would be obvious that the identified reference signals could be two signals and determining the time differences of arrival between the two signals.

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate step of

Application/Control Number: 10/531,038

Art Unit: 2618

determining based in part on a difference between the times of arrival of two of the plural signals at the geolocation system as taught by Kennedy into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to determine a mobile device without it having to be in the same communication network and does not need to be synchronized (Col. 2 lines 53-63).

Regarding claim 2, Stein et al. teaches wherein the first repeater is a tethered repeater (Section 0024).

Regarding claim 4, Stein et al. teaches wherein the time difference is approximately equal to a known repeater time delay (Sections 0028, 0045-0047, and 102-104).

Regarding claim 5, Stein et al. teaches wherein the first repeater attaches a tag to the mobile appliance's signal that passes through the first repeater and the step of determining if one of the plural signals has passed through the first repeater is based in part on the geolocation system operating on the tag (Sections 0007-0009 and 0039-0040).

Regarding claim 6, Stein et al. teaches the additional step of determining the location of the mobile appliance base in part on the determination of whether a signal received from the mobile appliance by the geolocation system has passed through the first repeater (Sections 0007-0009 and 0039-0040).

Regarding claim 9, Stein et al. teaches wherein the first repeater attaches a tag
to the mobile appliance's signal that passes through the first repeater and the step of
determining if one of the plural signals has passed through the first repeater is based in

part on the geolocation system operating on the tag (Sections 0007-0009 and 0039-0040).

Regarding claim 10, Stein et al. teaches the additional step of determining the location of the mobile appliance based in part on the determination of whether a signal received from the mobile appliance by the geolocation system has passed through the first repeater (Sections 0007-0009 and 0039-0040).

4. Claims 12, 14-17, 24, and 26-29 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stein et al. (US Pat Appl# 2003/0008663) in view of Kennedy et al. (US Pat Appl# 2004/0043775).

Regarding claim 12, Stein et al. teaches a method of determining the location of a mobile appliance in a wireless communication system having plural base stations 104a-c (Fig. 1A) and at least one repeater 114a (Fig. 1A) for communicating with the mobile appliance 106 (Fig. 1A), and a mobile positioning center 130 (Fig. 1A), and wherein the at least one repeater is connected with a communication tether to the base station (Section 0024), and the mobile position center provides mobile information to the geolocation system, the improvement comprising the step of monitoring the communication system with the geolocation system and determining if a target mobile appliance is served (identification code) by the at least one repeater (Sections 0007-0009 and 0039-0040), wherein the geolocation sensors monitor (identification code) the tether (Section 0024) between the at least one repeater and an antenna feed interface for the mobile appliance's signal (Sections 0007-0009 and 0039-0040). Stein et al. fails to teach a mobile positioning center.

Application/Control Number: 10/531,038

Art Unit: 2618

Kennedy et al. tasking and reporting method and implementation for wireless appliance location systems teaches a mobile positioning center 150 (Fig. 1).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a mobile positioning center as taught by Kennedy et al. into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to find geolocation of a mobile appliance that are under different interface protocol standards (Section 0016).

Regarding claim 14, Stein et al. teaches wherein the mobile appliance's signal is a traffic signal (Section 0025).

Regarding claim 15, Stein et al. teaches wherein the mobile appliance's signal is a reverse pilot signal (Section 0025).

Regarding claim 16, Stein et al. teaches wherein the mobile information is control information (Sections 0025, 0027, and 0037).

Regarding claim 17, Stein et al. teaches wherein the control information is call set up information or mobile registration process information (Sections 0025, 0027, and 0037).

Regarding claim 24, Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources teaches the limitations in claim 22. Stein et al. teaches the steps of locating the respective at least one repeater stations based on mobile information parameters received (Sections 0008 and 0039-0040) and using the location of the at least one repeater station to determine the

location of the target mobile appliance (Sections 0008 and 0039-0040). Stein et al. fails to teach a mobile positioning center.

Page 8

Kennedy et al. tasking and reporting method and implementation for wireless appliance location systems teaches a mobile positioning center 150 (Fig. 1).

Regarding claim 26, Stein et al. teaches a method for determining the location of a mobile appliance in a wireless communication system (Section 0007) having plural base stations 104a-c (Fig. 1A) and at least one repeater station 114a (Fig. 1A) for communicating with the mobile appliance 106 (Fig. 1A), wherein each of the at least one repeater station are connected to a respective one of the plural base stations with a communication tether (Section 0024), wherein the at least one translating repeater station relays a mobile appliance's signal on a different channel than the signal transmitted by the mobile appliance (Section 0116), the improvement comprising relaying from the at least one repeater station information regarding the channel of the mobile appliance's signal to a geolocation system and using the information to detect the mobile appliance's signal and calculate the mobile appliance's location (Sections 0007-0009 and 0116-0117). Stein is vague about locating a mobile appliance by a channel.

Kennedy teaches regarding the channel of the mobile appliance's signal to a geolocation system and using the information to detect the mobile appliance's signal and calculate the mobile appliance's location (Section 0005).

Regarding claim 27, Stein et al. teaches wherein the channel is defined by a frequency (Section 0116).

Regarding claim 28, Stein et al. teaches wherein the channel is defined by a time slot (Sections 0027 and 0044-0045).

Regarding claim 29, Stein et al. teaches wherein the channel is defined by a spreading code (Sections 0010 and 0044).

5. Claims 13 and 18-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stein et al. (US Pat Appl# 2003/0008663) in view of Kennedy et al. (US Pat Appl# 2004/0043775) and further in view of Tekinay (US Pat Pub# 2001/0027110).

Regarding claim 13, Stein et al. teaches a method of determining the location of a mobile appliance in a wireless communication system having plural base stations 104a-c (Fig. 1A) and at least one repeater 114a (Fig. 1A) for communicating with the mobile appliance 106 (Fig. 1A), and a mobile positioning center 130 (Fig. 1A), and wherein the at least one repeater is connected with a communication tether to the base station (Section 0024), and the mobile position center provides mobile information to the geolocation system, the improvement comprising the step of monitoring the communication system with the geolocation system and determining if a target mobile appliance is served (identification code) by the at least one repeater (Sections 0007-0009 and 0039-0040); and, adjusting the time of arrival of the mobile appliances signal based on the determination if the mobile appliance is being served by the one of the at least one repeaters (Sections 0026-0028, 0035, 0039-0040, and 0047). Stein et al. fails to teach a mobile positioning center and adjusting the time of arrival of the mobile appliances signal.

Kennedy et al. tasking and reporting method and implementation for wireless appliance location systems teaches a mobile positioning center 150 (Fig. 1).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a mobile positioning center as taught by Kennedy et al. into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to find geolocation of a mobile appliance that are under different interface protocol standards (Section 0016).

Stein and Kennedy fail to teach adjusting the time of arrival of the mobile appliances signal.

Tekinay teaches adjusting the time of arrival of the mobile appliances signal (Sections 0011 and 0028).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate adjusting the time of arrival of the mobile appliances signal as taught by Tekinay into a mobile positioning center as taught by Kennedy et al. into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to improve the accuracy of a geolocation system (Sections 0007-0008).

Regarding claim 18, Stein et al. teaches adjusting the time of arrival of the mobile signal at the geolocation sensor with known time delays of the at least one repeater and communication tether (Sections 0026-0028, 0035, 0039-0040, and 0047).

Regarding claim 19, Stein et al. teaches the step of adjusting the time of arrival of the mobile signal at another of the plural geolocation sensors with known time delays of another one of the at least one repeater and respective communication tether (Sections 00026-0028, 0035, 0039-0040, and 0047).

Regarding claim 20, Stein et al. teaches the step of accessing with the geolocation sensors the known time delays from a database 130 (Fig. 1A).

Regarding claim 21, Stein et al. teaches wherein the adjusted time of arrivals are used by the geolocation sensors in determining the location of the mobile appliance (Sections 0026-0028, 0035, 0039-0040, and 0047).

6. Claims 30-33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Stein et al. (US Pat Appl# 2003/0008663) in view of Kennedy et al. (US Pat Appl# 2004/0043775) and further in view of Hymel (US Pat# 6,246,336).

Regarding claim 30, Stein et al. teaches a method for determining the location of a mobile appliance in a wireless communication system (Section 0007) having plural base stations 104a-c (Fig. 1A) and plural repeaters 114a-c (Fig. 1A), wherein the repeaters relay the mobile appliances signal on the same channel as the channel in which the signal was received (Sections 0024-0025 and 0033), the improvement of using the first signal received from the mobile appliance at each of the plural base stations to determine the location of the mobile appliance (Sections 0008 and 0039-0040). Stein et al. fails to teach a mobile positioning center and disregarding a second signal.

Kennedy et al. teaches a mobile positioning center 150 (Fig. 1) provides mobile information to assist in the location of the mobile appliance (Sections 0026-0027).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a mobile positioning center as taught by Kennedy et al. into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to find geolocation of a mobile appliance that are under different interface protocol standards (Section 0016).

Stein and Kennedy fail to teach disregarding a second signal.

Hymel teaches disregarding a second signal received from the mobile appliance at each of the plural base stations 416 (Fig. 5).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate disregarding a second signal as taught by Hymel into a mobile positioning center as taught by Kennedy et al. into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to reduce errors (Col. 1 lines 41-55).

Regarding claim 31, Stein et al. further teaches wherein the channel is defined by a frequency (Section 0116).

Regarding claim 32, Stein et al. further teaches wherein the channel is defined by a time slot (Sections 0027 and 0044-0045).

Regarding claim 33, Stein et al. further teaches wherein the channel is defined by a spreading code (Sections 0010 and 0044).

7. Claim 34 is rejected under 35 U.S.C. 103(a) as being unpatentable over Stein et al. (US Pat Appl# 2003/0008663) in view of Bloebaum (US Pat# 6,188,351).

Regarding claim 34, Stein et al. apparatus for estimating the position of a terminal based on identification codes for transmission sources teaches a network overlay geolocation system for locating a mobile in a host wireless communication system (Section 0007), the host wireless communication system having a base station 104a-c (Fig. 1A) and a repeater station 114a (Fig. 1A) connected by a communication tether (Section 0024), the network overlay geolocation system comprising a geolocation sensor (sensing identification code and position of mobile device, Sections 0008 and 0039-0040) attached to the communication tether (Section 0024) between the base station 114a-c (Fig. 1A) and the repeater station 114a (Fig. 1A). Stein fails to clearly teach a geolocation sensor attached to the communication tether.

Bloebaum's improving signal acquisition in a global positioning system receiver teaches a geolocation sensor GPS (Fig. 1a) attached to a base station BTS sub 3 (Fig. 1a).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a geolocation sensor attached to the communication tether as taught by Bloebaum into Stein et al. apparatus for estimating the position of a terminal based on identification codes for

transmission sources in order to reduce latency in calculating the user's position (Col. 3 lines 54-63).

8. Claim 35 is rejected under 35 U.S.C. 103(a) as being unpatentable over Stein et al. (US Pat Appl# 2003/0008663) in view of Bloebaum (US Pat# 6,188,351) and further in view of Kennedy et al. (US Pat Appl# 2004/0043775).

Regarding claim 35, Stein et al. apparatus for estimating the position of a terminal based on identification codes for transmission sources teaches a base station 104a (Fig. 1a) and a repeater station 114a (Fig. 1a) interconnected by a communication tether (Section 0024); for providing mobile information; a network overlay geolocation system with a geolocation sensor co-located at the base station (sensing identification code and position of mobile device, Sections 0007-0008 and 0039-0040); wherein the tether is connected to the base station at an antenna feed interface (Section 0024). Stein et al. fails to teach a geolocation sensor located on the tether and mobile positioning center.

Bloebaum's improving signal acquisition in a global positioning system receiver teaches a geolocation sensor GPS (Fig. 1a) located on the tether prior to the interface (to a base station BTS sub 3 (Fig. 1a)).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a geolocation sensor located on the tether as taught by Bloebaum into Stein et al. apparatus for estimating the position of a terminal based on identification codes for transmission sources in order to reduce latency in calculating the user's position (Col. 3 lines 54-63).

Both Stein et al. and Bloebaum fail to teach a mobile positioning center.

Kennedy et al. tasking and reporting method and implementation for wireless appliance location systems teaches a mobile positioning center 150 (Fig. 1).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a mobile positioning center as taught by Kennedy et al. into a geolocation sensor as taught by Bloebaum into Stein et al. method for estimating the position of a terminal based on identification codes for transmission sources in order to find geolocation of a mobile appliance that are under different interface protocol standards (Section 0016).

Response to Arguments

9. Applicant's arguments with respect to claims 1-2, 4-6, 9-10, 12-24, and 26-35 have been considered but are most in view of the new ground(s) of rejection.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Andrew Wendell whose telephone number is 571-272-0557. The examiner can normally be reached on 7:30-5 M-F.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nay Maung can be reached on 571-272-7882. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/531,038 Page 16

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

WntNtฟ Wtmtฟฟ Andrew Wendell Examiner

Art Unit 2618

2/12/2007

NAY MAUNG SUPERVISORY PATENT EXAMINER